

OTFRIED SCHWARZKOPF

Atty. Docket No. 825-162

✓ Delete the paragraph starting at line 15 of page 1.

✓ Delete the paragraph starting on line 31 of page 1 and substitute therefor:

<sup>3</sup> The output of the coolant condenser can be continuously adjusted by way of the speed of a drive motor and in an especially energetically favourable manner, in the case of axial piston drive, by way of the piston stroke. Known axial piston drive or axial piston condensers for vehicle air conditioners comprise a drive shaft operated by way of a pulley. within a crank chamber a swash plate is supported on the drive shaft so that it is unrotatably fixed and can be tilted by way of a joint. The swash plate drives at least one piston that can move within a cylinder. In order to absorb tractive and pressure loads, each such piston is connected to the swash plate by way of two hinge yoke, one at the bearing surface of the swash plate that faces the piston and the other at the surface that faces away. With their flat surfaces contacting the bearing surfaces of the swash plate, the hinge yoke run at full circumferential velocity with a superimposed radial movement, which results in an elliptical track. The hinge yoke are seated with their rounded surfaces in sphere shaped formed bearings of the pistons, within which there is comparatively little relative movement during operation.

In the Claims:

✓ Claim 1 has been amended as follows:

<sup>sub</sup>  
<sup>152</sup>  
<sup>4</sup> 1. Axial piston drive with a continuously adjustable piston stroke, which comprises a drive shaft (10, 12, 170) and a swash plate (16, 18, 174) disposed in a bearing seat (14) that is positioned at a first tilt angle (22) with respect to the longitudinal direction (20) and on which the swash plate (16, 18, 174) is supported within a crank chamber (24), with a bore of bearing (30) that is tilted by a second tilt angle (28) with respect to the perpendicular line (26) of the swash plate (16, 18, 174), said swash plate (16, 18, 174) being rotatable through a range of angles by means of a controller (32, 34) in order to adjust the piston stroke, and also comprises at least one piston (44, 46, 48, 50) movably disposed in a cylinder (36, 38, 40, 42) and connected to the swash plate (16, 18, 174) so as to be driven thereby,

OTFRIED SCHWARZKOPF

Atty. Docket No. 825-162

sub  
B2

A4

characterized in that coupled to or superimposed upon the rotational movement from a maximal resulting tilt angle (52) to the minimal resulting tilt angle (54) is an axial stroke movement (56) of the swash plate (16, 18, 174) in the direction towards the piston (44, 46, 48, 50), and coupled to or superimposed upon the rotational movement from the minimal resulting tilt angle (54) to the maximal resulting tilt angle (52) is an axial stroke movement (116) of the swash plate in the direction away from the piston (44, 46, 48, 50).

✓ ✓ ✓ ✓ ✓ ✓  
Claim 4 has been amended as follows:

sub  
B2

Axial piston drive according to claim 1,  
characterized in that when turned through an angle of 180°, the swash plate (16, 18, 174) is shifted axially by a distance amounting to half a maximal piston stroke (60).

✓ ✓ ✓ ✓ ✓ ✓  
Claim 5 has been amended as follows:

Axial piston drive according to claim 1, characterized in that the swash plate (174) is rotatably seated in an axially sliding sleeve (178).

✓ ✓ ✓ ✓ ✓ ✓  
Claim 6 has been amended as follows:


5

Axial piston drive according to claim 1,  
characterized in that the controller (32) comprises a counterforce mechanism with at least one prestressed torsion spring (62, 64, 66, 68) that acts on the swash plate (16, 174).

✓ ✓ ✓ ✓ ✓ ✓  
Claim 7 has been amended as follows:

Axial piston drive according to claim 1,  
characterized in that the controller (34) comprises an adjustment unit (70) that is separate from the piston (44, 46, 48, 50).

Respectfully submitted,

  
\_\_\_\_\_  
Gary A. Essmann  
(Reg. No. 29,376)

ANDRUS, SCEALES, STARKE & SAWALL, LLP  
100 East Wisconsin Avenue, Suite 1100  
Milwaukee, Wisconsin 53202  
(414) 271-7590  
Atty. Docket No. 825-162


CERTIFICATE OF EXPRESS MAIL

I hereby certify that this correspondence is being deposited with the United States Postal Service, with sufficient postage, as EXPRESS MAIL - POST OFFICE ADDRESSEE, in an envelope addressed to: Commissioner for Patents, Washington, D.C. 20231 on the 15th day of February, 2002. The Express Label is EL812734014US.

\_\_\_\_\_  
Marlene Kubiak

Name

Reg. No.

\_\_\_\_\_  
Signature

February 15, 2002

\_\_\_\_\_  
Date